



TEST REPORT

Product Name: LoRa Module
FCC ID: 2ATPO-RA01SCP
Trademark:  
Model Number: Ra-01SC-P
Prepared For: Shenzhen Ai-Thinker Technology Co., Ltd
Address: 410, Block C, Huafeng Smart Innovation Port. Gushu 2nd Road, Gushu Community, Xixiang Street, Baoan District, Shenzhen, China
Manufacturer: Shenzhen Ai-Thinker Technology Co., Ltd
Address: 410, Block C, Huafeng Smart Innovation Port. Gushu 2nd Road, Gushu Community, Xixiang Street, Baoan District, Shenzhen, China
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: Oct. 29, 2024
Sample tested Date: Oct. 29, 2024 to Nov. 18, 2024
Issue Date: Nov. 18, 2024
Report No.: CTB24102904806RF01
Test Standards: FCC CFR Title 47 Part 15 Subpart C Section 15.231
ANSI C63.10:2013
Test Results: PASS
Remark: This is 433MHz radio test report.

Compiled by:

Reviewed by:

Approved by:

Zhou kui

Arron Liu



Zhou Kui

Arron Liu

Bin Mei / Director

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report r Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration	Page
1. VERSION	4
2. TEST SUMMARY	5
3. MEASUREMENT UNCERTAINTY	6
4. PRODUCT INFORMATION AND TEST SETUP	7
4.1 Product Information	7
4.2 Test Setup Configuration	7
4.3 Support Equipment	7
4.4 Test Mode	8
4.5 Test Environment	8
4.6 Test Channel	8
5. TEST FACILITY AND TEST INSTRUMENT USED	9
5.1 Test Facility	9
5.2 Test Instrument Used	9
6. AC POWER LINE CONDUCTED EMISSION	11
6.1 Block Diagram Of Test Setup	11
6.2 Limit	11
6.3 Test procedure	11
6.4 Test Result	13
7. RADIATED EMISSION	14
7.1 Block Diagram Of Test Setup	14
7.2 Limit	14
7.3 Test procedure	15
7.4 Test Result	17
8. DWELL TIME	28
8.1 Block Diagram Of Test Setup	28
8.2 Limit	28
8.3 Test procedure	28
8.4 Test Result	29
9. OCCUPIED BANDWIDTH	31
9.1 Block Diagram Of Test Setup	31
9.2 Limit	31

9.3	Test procedure	31
9.4	Test Result	32
10.	ANTENNA REQUIREMENT	34
11.	EUT TEST SETUP PHOTOGRAPHS	35

(Note: N/A means not applicable)



1. VERSION

Report No.	Issue Date	Description	Approved
CTB24102904806RF01	Nov. 18, 2024	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	N/A
Radiated Emission	47 CFR Part 15 Subpart C Section 15.209; 15.231(b)	ANSI C63.10-2013	PASS
Dwell Time	47 CFR Part 15 Subpart C Section 15.231 (a)	ANSI C63.10-2013	PASS
Occupied Bandwidth	47 CFR Part 15 Subpart C Section 15.231(c)	ANSI C63.10-2013	PASS
Antenna requirement	47 CFR Part 15 Subpart C Section 15.203	ANSI C63.10-2013	PASS

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in C ISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Item	Uncertainty
Occupancy bandwidth	$U=\pm 54.3\text{Hz}$
Conducted output power Above 1G	$U=\pm 1.0\text{dB}$
Conducted output power below 1G	$U=\pm 0.9\text{dB}$
Power Spectral Density , Conduction	$U=\pm 1.0\text{dB}$
Conduction spurious emissions	$U=\pm 2.8\text{dB}$
Out of band emission	$U=\pm 54\text{Hz}$
3m chamber Radiated spurious emission(30MHz-1GHz)	$U=\pm 4.3\text{dB}$
3m chamber Radiated spurious emission(1GHz-18GHz)	$U=\pm 4.5\text{dB}$
humidity uncertainty	$U=\pm 5.3\%$
Temperature uncertainty	$U=\pm 0.59^{\circ}\text{C}$
Supply voltages	$U=\pm 3\%$
Time	$U=\pm 5\%$

4. PRODUCT INFORMATION AND TESTSETUP

4.1 ProductInformation

Model(s): Ra-01SC-P

Model Description: N/A

Hardware Version: V1.0

Software Version: V1.0

Operation Frequency: 410-525MHz

Type of Modulation: ASK

Antenna installation: External antenna

Antenna Gain: 1.0dBi

Ratings: DC 3.3V powering from PC

4.2 Test SetupConfiguration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 SupportEquipment

Item	Equipment	Mfr/Brand	Model/TypeNo.	SeriesNo.	Note
1.	Laptop	DELL	Vostro 5490	N/A	AE

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test mode
Keep the EUT in transmitting mode with modulation.

4.5 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(DC):	3.3
Normal Temperature(°C)	23

4.6 Test Channel

Channel	Frequency (MHz)
01	410MHz
02	411MHz
...	...
58	467MHz
59	468MHz
...	...
115	524 MHz
116	525 MHz

5. TEST FACILITY AND TEST INSTRUMENT USED**5.1 Test Facility**

All measurement facilities used to collect the measurement data are located at Floor 1&2, Building A, No. 26 of Xinhe Road, Xinqiao Street, Baoan District, Shenzhen China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

5.2 Test Instrument Used

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2025/6/28
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2025/6/28
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2025/6/28
4	Communication test set	R&S	CMW500	108058	V3.5.80	2025/6/28
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2025/6/28
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2025/6/28
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2025/6/28
9	2.4 GHz Filter	Shenxiang	MSF2400- 2483.5MS- 1154	20181015001	/	2025/6/30
10	5 GHz Filter	Shenxiang	MSF5150- 5850MS- 1155	20181015001	/	2025/6/30
11	Filter	Xingbo	XBLBQ- DZA120	190821-1-1	/	2025/6/30
12	BT&WI-FI Automatic test software	Microwave	MTS8310	Ver. 2.0.0.0	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2025/6/28
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	/	2025/6/28
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/	/
16	966 chamber	C.R.T.	966	/	/	2027/6/21
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7 (104489/003)	2025/6/28
18	Amplifier	HP	8447E	2945A02747	/	2025/6/28
19	Amplifier	Agilent	8449B	3008A01838	/	2025/6/28
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2025/6/28
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2025/6/28
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/28
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/

25	40G Horn antenna	A/H/System	SAS-574	588	/	2025/6/28
26	Amplifier	AEROFLEX	Aeroflex	097	/	2025/6/28
27	Power Metter	KEYSIGHT	N1912AP	N/A	A.05.00	2025/6/28

Continuous disturbance


No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2027/6/21
2	AMN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/6/30
3	Pulse limiter	ROHDE&SCHWARZ	ESH3Z2	357881052	/	2025/6/28
4	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2025/6/30
5	Coaxial cable	ZDECL	Z302S	18091904	/	2025/6/30
6	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/30
7	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2024/11/16
8	EZ-EMC	Frad	EMC-con3A1.1	/	/	/
9	Current Probe	FCC	F-52B	199453	/	2025/5/27
10	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/6/28
11	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28

Radiated emission(No.2 Chamber)

No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2026/11/14
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2026/7/07
3	Broadband Antenna	Schwarzbeck	VULB 9168	1471	/	2025/7/06
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/30
5	Preamplifier	Schwarzbeck	BBV 9743 B	00500	/	2025/5/23
6	EMI TEST RECEIVER	R&S	ESCI7	100861	/	2024/11/27
7	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
8	EMI test software	Farad	EZ-EMC	/	Ver. FARAD-3A1+	/
9	Coaxial cable	Rosenberg	8m	/	/	2024/11/27
10	Coaxial cable	Times	2m	/	/	2024/11/27
11	Coaxial cable	Times	2m	/	/	2024/11/27
12	Coaxial cable	Times	1m	/	/	2024/11/27
13	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/29
14	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/6/28
15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28

6. AC POWER LINE CONDUCTED EMISSION

6.1 Block Diagram Of Test Setup



6.2 Limit

* Decreasing linearly with the logarithm of the frequency

Frequency (MHz)	Maximum RF Line Voltage (dB μ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50


6.3 Test procedure

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


6.4 Test Result

L:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV	dBuV	dB	
1	*	0.1500	49.40	10.89	60.29	66.00	-5.71	QP
2		0.1500	32.21	10.89	43.10	56.00	-12.90	AVG
3		0.2280	35.82	10.69	46.51	62.52	-16.01	QP
4		0.2280	19.77	10.69	30.46	52.52	-22.06	AVG
5		0.4660	27.17	10.52	37.69	56.58	-18.89	QP
6		0.4660	15.05	10.52	25.57	46.58	-21.01	AVG
7		1.4580	25.29	11.24	36.53	56.00	-19.47	QP
8		1.4580	18.28	11.24	29.52	46.00	-16.48	AVG
9		15.9900	17.49	13.39	30.88	60.00	-29.12	QP
10		15.9900	5.47	13.39	18.86	50.00	-31.14	AVG
11		26.8300	19.35	14.19	33.54	60.00	-26.46	QP
12		26.8300	8.83	14.19	23.02	50.00	-26.98	AVG

N:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1	*	0.1500	49.17	10.89	60.06	66.00	-5.94	QP
2		0.1500	27.22	10.89	38.11	56.00	-17.89	AVG
3		0.1955	40.85	10.73	51.58	63.80	-12.22	QP
4		0.1955	24.85	10.73	35.58	53.80	-18.22	AVG
5		0.3140	32.63	10.63	43.26	59.86	-16.60	QP
6		0.3140	18.39	10.63	29.02	49.86	-20.84	AVG
7		1.4580	26.92	11.24	38.16	56.00	-17.84	QP
8		1.4580	19.37	11.24	30.61	46.00	-15.39	AVG
9		12.9140	16.88	13.30	30.18	60.00	-29.82	QP
10		12.9140	7.48	13.30	20.78	50.00	-29.22	AVG
11		28.0860	20.03	14.31	34.34	60.00	-25.66	QP
12		28.0860	11.46	14.31	25.77	50.00	-24.23	AVG

Remark:

Factor = Cable loss + LISN factor, Margin = Measurement – Limit All modes have been tested with only the worst data 411MHz

7. RADIATED EMISSION

7.1 Block Diagram Of Test Setup

Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz

7.2 Limit

Spurious Emissions:

Frequency	Field strength (dB μ V/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	$20\log 2400/F$ (kHz) + 80	-	3
0.490MHz-1.705MHz	$20\log 24000/F$ (kHz) + 40	-	3
1.705MHz-30MHz	$20\log 30 + 40$	-	3
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-960MHz	46.0	Quasi-peak	3
960MHz-1GHz	54.0	Quasi-peak	3
Above 1GHz	54.0	Average	3

Note: 15. 35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Field Strength of Fundamental Limit:

Fundamental and harm onics emission limits Frequency(MHz)	Field strength of Fundamental((microvolts/meter)	Field strength of spurious emissions(microvolts/meter)
40.66-40.70	2280	225
70-130	1250	125
130-174	1250 to 3750**	125 to 375**
174-260	3750	375
260-470	3750 to 12500**	375 to 1250**
Above 470	12500	1250

** linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

Frequency	Limit (dB $\mu\text{V/m}$ @3m)	Remark
410MHz	80	Average Value
	100	Peak Value
467MHz	81.85	Average Value
	101.85	Peak Value
525MHz	81.94	Average Value
	101.94	Peak Value

7.3 Test procedure

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotating table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi-Anechoic Chamber to fully Anechoic Chamber and change from table 0.8 meter to 1.5 meter (Above 18GHz the distance is 1 meter and table is 1.5 meter).
- Test the EUT in the lowest channel, the middle channel, the Highest channel
- Repeat above procedures until all frequencies measured was complete.

Receiver

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30KHz	Average

set:

0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average


7.4 Test Result

Calculation of average factor


The output field strengths of specification in accordance with the FCC rules specify measurements with an average detector. During the test, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The duty cycle is measured in 100 ms or the repetition cycle period, whichever is a shorter time frame. The duty cycle is measured by placing the spectrum analyzer to set zero span at 100kHz resolution bandwidth.


410 MHz



467 MHz



525 MHz



Duty cycle = T on time / T period = 100%
PDCF = 0

Radiated Spurious Emission**Frequency Range (9 kHz-30MHz)**

Frequency (MHz)	Level@3m (dBμV/m)	Limit@3m (dBμV/m)
--	--	--
--	--	--
--	--	--
Note: 1. <i>Emission Level=Reading+ Cable loss-Antenna factor-Amp factor</i>		--


2. *The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement*

About 30MHz-1GHz

Test Results: 410MHz


Antenna polarity: H

90.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	68.3907	50.64	-17.31	33.33	40.00	-6.67	QP
2 !	175.0365	53.97	-15.13	38.84	43.50	-4.66	QP
3	247.6818	53.48	-16.43	37.05	46.00	-8.95	QP
4 *	411.8240	88.25	-12.04	76.21	100.00	-23.79	peak
5	537.5891	34.12	-8.22	25.90	46.00	-20.10	QP
6 X	821.7103	56.18	-2.20	53.98	80.00	-26.02	peak

Antenna polarity: V



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 !	68.3907	52.95	-17.31	35.64	40.00	-4.36	QP
2 !	173.2050	53.63	-14.85	38.78	43.50	-4.72	QP
3 *	411.8240	88.35	-12.04	76.31	100.00	-23.69	peak
4	492.4685	40.32	-9.50	30.82	46.00	-15.18	QP
5 X	821.7103	55.44	-2.20	53.24	80.00	-26.76	peak
6	929.0081	30.86	-0.41	30.45	46.00	-15.55	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit - Level

467MHz

Antenna polarity: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 !	68.3908	54.14	-17.31	36.83	40.00	-3.17	QP
2 !	155.9101	51.64	-13.23	38.41	43.50	-5.09	QP
3 !	175.0367	55.47	-15.13	40.34	43.50	-3.16	QP
4	210.7860	52.70	-16.91	35.79	43.50	-7.71	QP
5 *	467.2350	89.42	-10.31	79.11	101.85	-22.74	peak
6 X	932.2713	58.13	-0.42	57.71	81.85	-24.14	peak

Antenna polarity: V




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 !	68.3906	52.95	-17.31	35.64	40.00	-4.36	QP
2 !	176.8876	54.36	-15.42	38.94	43.50	-4.56	QP
3	225.3080	49.49	-16.72	32.77	46.00	-13.23	QP
4 *	467.2350	90.15	-10.31	79.84	101.85	-22.01	peak
5	526.3967	40.32	-8.53	31.79	46.00	-14.21	QP
6 X	932.2713	55.33	-0.42	54.91	81.85	-26.94	peak

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit - Level


525MHz

Antenna polarity: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 !	68.1514	54.08	-17.24	36.84	40.00	-3.16	QP
2 !	156.4578	51.24	-13.24	38.00	43.50	-5.50	QP
3 !	170.1948	56.03	-14.39	41.64	43.50	-1.86	QP
4	234.1684	54.53	-16.61	37.92	46.00	-8.08	QP
5	420.5803	37.53	-11.77	25.76	46.00	-20.24	QP
6 *	524.5540	83.92	-8.59	75.33	101.94	-26.61	peak

Antenna polarity: V



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 !	68.3908	52.45	-17.31	35.14	40.00	-4.86	QP
2	154.8204	47.78	-13.21	34.57	43.50	-8.93	QP
3 !	168.4138	52.90	-14.20	38.70	43.50	-4.80	QP
4	212.2695	47.70	-16.89	30.81	43.50	-12.69	QP
5	370.7023	39.98	-12.81	27.17	46.00	-18.83	QP
6 *	524.5540	84.98	-8.59	76.39	101.94	-25.55	peak

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit - Level

For average Emission

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
410	76.21	0	76.21	80	-3.79	Horizontal
467	79.11	0	79.11	81.85	-2.74	Horizontal
525	75.33	0	75.33	81.94	-6.61	Horizontal
820	53.98	0	53.98	60	-6.02	Horizontal
934	57.71	0	57.71	61.85	-4.14	Horizontal
410	76.31	0	76.31	80	-3.69	Vertical
467	78.84	0	78.84	81.85	-3.01	Vertical
525	76.39	0	76.39	81.94	-5.55	Vertical
820	53.24	0	53.24	60	-6.76	Vertical
934	54.94	0	54.94	61.85	-6.91	Vertical

Notes: Average emission Level = Peak Level + Duty cycle factor

Above 1GHz Test Results

410MHz

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit		Margin dB		Polarization
				PK	AV	PK	AV	
820	50.78	0	50.78	80	60	-29.22	-9.22	Vertical
1230	46.38	0	46.38	80	60	-33.62	-13.62	Vertical
1640	43.11	0	43.11	80	60	-36.89	-16.89	Vertical
2050	42.75	0	42.75	80	60	-37.25	-17.25	Vertical
2460	40.14	0	40.14	80	60	-39.86	-19.86	Vertical
2870	41.70	0	41.70	80	60	-38.30	-18.30	Vertical
1640	49.26	0	49.26	80	60	-30.74	-10.74	Horizontal
2460	47.81	0	47.81	80	60	-32.19	-12.19	Horizontal
3280	43.89	0	43.89	80	60	-36.11	-16.11	Horizontal
4100	40.87	0	40.87	80	60	-39.13	-19.13	Horizontal
4920	41.32	0	41.32	80	60	-38.68	-18.68	Horizontal
5740	41.01	0	41.01	80	60	-38.99	-18.99	Horizontal

Notes: Average emission Level = Peak Level + Duty cycle factor

467MHz

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit		Margin dB		Polarization
				PK	AV	PK	AV	
1050	50.03	0	50.03	81.85	61.85	-31.82	-11.82	Vertical
1575	48.10	0	48.10	81.85	61.85	-33.75	-13.75	Vertical
2100	44.97	0	44.97	81.85	61.85	-36.88	-16.88	Vertical
2625	40.33	0	40.33	81.85	61.85	-41.52	-21.52	Vertical
3150	41.12	0	41.12	81.85	61.85	-40.73	-20.73	Vertical
3675	41.82	0	41.82	81.85	61.85	-40.03	-20.03	Vertical
2100	50.60	0	50.60	81.85	61.85	-31.25	-11.25	Horizontal
3150	47.58	0	47.58	81.85	61.85	-34.27	-14.27	Horizontal
4200	44.62	0	44.62	81.85	61.85	-37.23	-17.23	Horizontal
5250	42.83	0	42.83	81.85	61.85	-39.02	-19.02	Horizontal
6300	41.83	0	41.83	81.85	61.85	-40.02	-20.02	Horizontal
7350	40.14	0	40.14	81.85	61.85	-41.71	-21.71	Horizontal

Notes: Average emission Level = Peak Level + Duty cycle factor


525MHz

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit		Margin dB		Polarization
				PK	AV	PK	AV	
1050	49.45	0	49.45	81.94	61.94	-32.49	-12.49	Vertical
1575	47.98	0	47.98	81.94	61.94	-33.96	-13.96	Vertical
2100	44.50	0	44.50	81.94	61.94	-37.44	-17.44	Vertical
2625	43.01	0	43.01	81.94	61.94	-38.93	-18.93	Vertical
3150	41.54	0	41.54	81.94	61.94	-40.40	-20.40	Vertical
3675	40.36	0	40.36	81.94	61.94	-41.58	-21.58	Vertical
2100	49.39	0	49.39	81.94	61.94	-32.55	-12.55	Horizontal
3150	47.71	0	47.71	81.94	61.94	-34.23	-14.23	Horizontal
4200	44.94	0	44.94	81.94	61.94	-37.00	-17.00	Horizontal
5250	43.12	0	43.12	81.94	61.94	-38.82	-18.82	Horizontal
6300	41.73	0	41.73	81.94	61.94	-40.21	-20.21	Horizontal
7350	41.19	0	41.19	81.94	61.94	-40.75	-20.75	Horizontal

Notes: Average emission Level = Peak Level + Duty cycle factor

8. DWELL TIME

8.1 Block Diagram Of Test Setup



8.2 Limit

According to FCC 15.231(a) requirement:

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.


8.3 Test procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

8.4 Test Result


410MHz

Transmitting time(S)	Limit (S)	Results
0.712	≤5	Pass




467MHz

Transmitting time(S)	Limit (S)	Results
0.712	≤5	Pass




525MHz

Transmitting time(S)	Limit (S)	Results
0.712	≤5	Pass



9. OCCUPIED BANDWIDTH

9.1 Block Diagram Of Test Setup



9.2 Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

B.W (20dBc) Limit = $0.25\% \times f(\text{MHz}) = 0.25\% \times 411\text{MHz} = 1.0275\text{MHz}$ B.W (20dBc)

Limit = $0.25\% \times f(\text{MHz}) = 0.25\% \times 467\text{MHz} = 1.1675\text{MHz}$ B.W (20dBc) Limit = 0.25%

$\times f(\text{MHz}) = 0.25\% \times 525\text{MHz} = 1.3125\text{MHz}$


9.3 Test procedure

1. Set RBW = 10 kHz.
2. Set the video bandwidth (VBW) \geq RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

9.4 Test Result


410MHz

20dB bandwidth (kHz)	Limit (MHz)	Results
137.0	1.0275	Pass




467MHz

20dB bandwidth (kHz)	Limit (MHz)	Results
139.6	1.1675	Pass



525MHz

20dB bandwidth (kHz)	Limit (MHz)	Results
136.9	1.3125	Pass



10. ANTENNA REQUIREMENT

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


EUT Antenna:

The antenna is External antenna and no consideration of replacement. The best case gain of the antenna is 1.0dBi.

11. EUT TEST SETUP PHOTOGRAPHS

Radiated Emissions

Below 1G



Above 1G



Conducted emission



***** END OF REPORT *****